

## Command "parameters" (not obligatory)

<d><type><CustomerVATNo><Beneficiary><InvFree1><InvFree2><InvFree3> <InvFree4[20]><Address[30]>

data fields:

d	1	byte command - 'd'
type	1	byte command type ASCII '0'
CustomerVATNo	15	15 symbols Customer VAT registration number
Beneficiary	30	30 symbols Recipient name
InvFree1	20	20 symbols free text line
InvFree2	20	20 symbols free text line
InvFree3	20	20 symbols free text line
InvFree4	20	20 symbols free text line
Address	30	30 symbols Address

ECR response: ACK or NACK

notes: This command should be right next the "start" command.

## Command "sale-article" :

<p><name><sum><decimal point><quantity><VAT Group><department>{<group>}

data fields:

p	1	byte command - 'p'
name	24	ASCII characters, including digits, capital Latin and Cyrillic letters as article description including symbol for LF=7Ch - ' ' or separator for MU=80h or 60h followed up to 3 symbols for unit.
sum	8	bytes sum (no decimal point) ASCII format
decimal point	1	byte decimal point position - ASCII number '0' or '2' '0' = no decimal point, sum = XXXXXXXX '2' = decimal point position 2, sum = XXXXXX.XX
quantity	9	ASCII digits XXXXXXXXX, equal to quantity sold - XXXXXX.XXX
VAT Group	1	byte VAT Group - ASCII number '0' .. '5' '0','5' – no tax; '1' - group 'A'; '2' - group 'B'; '3' - group 'C'; '4' - group 'D'
department	1	byte department number of the sell. ASCII number '0' to '9'
group	1	byte group number of the sell. ASCII number '0' to '9'

ECR response: ACK or NACK